

XS-IPPT400ATA-4U-SPIR-SOLAR

PT IP Camera 4G Solar Power 4 Mpx
1/2.8" STARVIS CMOS 5Mpx
Dual Light: IR and White Light
Human detection with active
deterrence
Compression
H.265+/H.265/H.264+/H.264
Sound and light alarm | PIR



X-Security

Solar PT IP camera 4G
1/2.8" STARVIS™ CMOS
4 Megapixel Fixed lens 4mm
White light up to 30m
IR up to 30m
DWDR
PIR
Maximum power of the solar module 5,5W
Bidirectional audio
Built-in microphone and speaker
Audio
Alarms
MicroSD card recording up to 512GB
Human detection with active deterrence
Alarm sound and light
Average speed 62º/segundo
H.265+
RJ-45 10/100 BaseT
WEB, CMS, Smartphone and NVR interface
ONVIF Compatible
Weatherproof IP66

Specifications

Brand	X-Security
Image sensor	1/2.8" STARVIS CMOS
Maximum resolution	4 Megapixel (2560x1440)
Main Stream rate	4M / 1080p / 1.3M / 720p @ (1–25/30 fps)
Compression	D1/CIF/VGA@ (1–25/30 fps)
Lens	4 mm (H: 84° V: 42° D: 101°)
Minimum illumination	Colour: 0.05 lux@F1.6 B/W: 0.005 lux@F1.6 0 lux@F1.6 (illuminator on)
Image improvements	DWDR, BLC, HLC, AWB, AGC, 3D-NR, IVS, ROI, Privacy Masking
Active light deterrence	Warning white light Flash duration: 5 s–30 s Frequency of the flash: high, medium, low
Active sound deterrent	1 audible warning alarm The alarm can be set to sound 1-3 times
Network port	RJ-45 (10/100 Base-T)
4G	Integrated
Frequency band	LTE-FDD: B1/3/5/7/8/20/28 LTE-TDD: Band 38/40/41 WCDMA: Band 1/5/8 GSM: 850/900/1800 MHz
Method of transmission	Unicast/Multicast
Internal memory	Slot for MicroSD Card, Max 512GB
Audio	Two-way audio and (built-in microphone and speaker)
Solar Module	Maximum power 5,5 W Cell type Monocrystalline Temp. operating –40 °C +80 °C Dimensions 224 × 195 × 44 mm
Battery	Lithium ions Capacity 10 Ah Max. load voltage. 4,2 V Battery voltage 3,6 V Battery life 500 cycles Life cycle 7 days (at a rate of 1 hour of live remote viewing per day)
Remote access	Web browser, CMS Software (DSS/PSS), Smartphone (DMSS) and NVR
Audio Compression	G.711a; G.711Mu; G.726; PCM
Interoperability	ONVIF (S&G&T Profile); .CGI; SDK; P2P
Power	DC 12 V / 1,5 A
Temp. operation	-30° C ~ +60° C
Degree of protection	Weatherproof IP66
Dimensions	336 mm × 247 mm × 223 mm
Weight	1,4 Kg
Protection	P66, TVS 2000 V lightning-proof; surge protection; transient voltage protection