

XS-IPB040A-4YWSOLARPIR-4G

4G Bullet Camera

1/3" 4MP progressive CMOS

2.8mm / WDR Lens

Includes photovoltaic panel for
autonomous use

Includes rechargeable lithium battery

Weatherproof IP67



X-Security

1/3" of 4 MP CMOS image sensor, low luminance and high definition image

Max. outputs. 4 MP (2688 x 1520) to 25/30 fps

Codec H.265

Warm light/built-in IR LED

Light and sound alarm link

Integrated 4G module

Built-in PIR sensor

8 eMMC memory chip of [%VAR%] GB built-in

Stand-alone with built-in solar panel and battery

Anomaly detection

Supports max. Micro SD card of 256G

Built-in microphone and speaker

Protection IP67.

Specifications

Brand	X-Security
Image sensor	1/3" 4MP progressive CMOS
Maximum resolution	4 Megapixel (2688x1520)
Minimum illumination	0,01 lux to F1,6 (color, 30 IRE)
Lens	2,8 mm: height: 102°; V: 54°; D: 121°
Bitrate	H.265: 32 kbps–6144 kbps H.264: 32 kbps–6144 kbps
Main Stream rate	4M (2688 × 1520); 4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1,3 M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Compression	H.265 / H264
Image improvements	WDR (120dB), BLC, 3D-DNR, MD, ROI
Alarm Events	Motion detection; video manipulation; audio detection; security exception; PIR alarm; low-battery alarm; light alarm; alarm sound
Day / Night	Removable mechanical ICR filter
Internal memory	MicroSD card, Max 256 GB
Network interface	Ethernet 10M / 100M 4G Micro SIM card (LTE-TDD/LTE-FDD/WCDMA/GSM)
Audio	Built-in microphone
Remote access	WEB, CMS (DSS/PSS), Smartphone and NVR interface
Interoperability	ONVIF
Consumption	Sleep mode: 0,03 W General mode: 2,1 W Max. (4G pulling current+IR+speaker+warning light): 4 W
Battery	Lithium 10Ah Battery voltage (3.0 V - 4.2 V)
Degree of protection	IP67
Material	metal + plastic
Temp. operation	−20 °C to +60 °C (−4 °F to +140 °F)
Base dimensions	238 mm × 181 mm × 296 mm (9,37" × 7,13" × 11,65")
Weight	1250 g