

SF-IPD360A-6I1

Safire Smart

Fisheye IP dome camera I1 range

Resolution 6 Megapixel (2160x2160)

Lens 1.1 mm, wide-angle 360°

Audio, Alarms, MicroSD Card 256GB

Waterproofing IP67 | PoE

(IEEE802.3af)



Safire Smart

Range I1 fisheye

Fisheye IP Dome Camera

1/2.9" Progressive Scan CMOS

6 Megapixel (2160x2160)

1.1 mm Lens

Wide-angle 360°

0 Lux

IR Range 30 m

Compression H.265 / H.264

WDR

3DNR

Integrated microphone

Audio

Alarms

MicroSD card up to 256GB

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

Specifications

Brand	Safire Smart
Range	I1
Image sensor	1/2.9" Progressive Scan CMOS
Maximum resolution	6 Megapixel (2160x2160)
Minimum illumination	Colour: 0.068 Lux @(F2.0, AGC ON), 0 Lux with IR
IR range	30 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Resolution	- Fisheye + panorama + 3 PTZ 25fps@(2160x2160 / 1920x1920 / 1440x1440 / 960x960 / 480x480) 3x 15fps@(1920x1080 / 704x576), 15fps@(960x540 / 480x240) - Fisheye + 4 PTZ 50Hz: 25fps@(2160x2160 / 1920x1920 / 1440x1440 / 960x960 / 480x480) 4x 15fps@(960x 540 / 480x240)
Compression	H.265 / H.264 / MJPEG
Bitrate	64 Kbps - 8 Mbps
Lens	1.1 mm (360°)
Installation	Ceiling or Wall
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Audio	Integrated microphone, 1 input and 1 output
Audio Compression	G711A / U
Alarms	1 Input / 1 Relay
Video output	1 BNC CVBS output
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / 950 mA / 10.5 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	130 (?) x 41 (Fo) mm
Weight	650 g