

# SF-IPB585ZA-4I1-0722

Safire Smart

Bullet IP camera range I1 AI

Advanced

Resolution 4 Megapixel (2592x1520)

Motorized Lens 7-22 mm | Audio | IR

100m

Advanced AI: Perimeter, Facial,

Counting, Metadata

Waterproofing IP67 | PoE

(IEEE802.3af) | Alarm



Safire Smart

Range I1 with Advanced Artificial Intelligence

Bullet IP camera

1/3" Progressive Scan CMOS

4 Megapixel (2592x1520)

7-22mm motorised lens

0 Lux

IR Range 100 m

Compression H.265+ / H.264+

WDR

3DNR

Audio

Alarms

Advanced Artificial Intelligence: human, vehicle and non-motorized vehicle detection

Facial Capture

Video metadata

Human, vehicle and non-motorized vehicle counts

WEB, CMS, Smartphone and NVR interface

ONVIF Compatible

PoE (IEEE802.3af)

Weatherproof IP67

# Specifications

---

Brand	Safire Smart
Range	I1
Image sensor	1/3" Progressive Scan CMOS
Maximum resolution	4 Megapixel (2592x1520)
Minimum illumination	Colour: 0.005 Lux @(F1.6, AGC ON), 0 Lux with IR
IR range	100 m
Day/Night	Removable mechanical ICR filter
Electronic Shutter	1/2~1/100.000 s
Main Stream rate	25 FPS (4Mpx, 2K, 3Mpx, 1080P, 720P) HFR mode: 60 FPS (1080P / 720P)
Extra Stream rate	25 FPS (720P, D1, CIF, 480x240)
Third Stream Rate	25 FPS (D1, 480x240, CIF)
Compression	H.265+ / H.265 / H.264+ / H.264
Bitrate	64 Kbps ~ 8 Mbps
Lens	Motorized 7 ~ 22 mm
Viewing Angle (FOV)	H: 43-18°, V: 25-11°, D: 50-20°
Range performance	W: 137 m (D), 55 m (O), 24 m (R), 14 m (I) T: 316 m (D), 126 m (O), 63 m (R), 32 m (I)
Image improvements	WDR, BLC, HLC, 3D-DNR, AWB, ROI, Mirror Function, Privacy Mask, ROI
Motion Detection	Yes
Smart Features	Advanced artificial intelligence based on human, vehicle, and non-motorized vehicle classification on: Area Intrusion, Line Crossing, Entry Region, Exit Region  Face Detection and Face Capture  Counting of people, vehicles and non-motorized vehicles  Feature extraction: - Human: Up to 13 characteristics - Vehicle: Up to 5 characteristics - Non-motorized vehicle: Up to 1 characteristics  Other smart events: dropped object, removed object, Video exceptions (change of scene, video loss, ...)
Audio	1 Input
Audio Compression	G711A / U
Alarms	1 Input / 1 Relay
CVBS output	Yes (BNC for test)
Network interface	Ethernet 10 / 100M BaseT
Internal memory	MicroSD card up to 256GB
Remote access	Web Browser, Smartphone App Safire Smart, PC Software Safire Smart VMS
Interoperability	ONVIF
Power	DC 12 V / mA / 9 W max. / IEEE802.3af PoE
Degree of protection	Weatherproof IP67
Material	Metallic
Temp. operation	-30° C ~ +60° C
Dimensions	88.7 (H) x 100.2 (W) x 278.3 (D) mm
Weight	1000 g