

# UPS1000VA-ON-2-RACK

Online UPS for rack or tower  
installation

Power 1000VA/900W

2 surge protected outputs

Recharge time 4h 90%

Hot swappable

2 sealed lead-acid batteries



UPS online

Power1000 VA / 900 W

90% Efficiency

Entry 220~240 VAC

2 salidas backup con protección SAI

2 12 V 9.5 Ah sealed maintenance-free lead-acid batteries

Recharge time 4~5 h

Special format to be installed in a rack using UPS-RACK-KIT (not included)

Emergency Power Off (EPO) function

Cold start

# Specifications

Power	1000VA/900W
Input voltage	220-240 Vac
Output voltage	220-240 Vac
Power factor	0.98
Harmonic Distortion	23% THD (Linear load) 25% THD (Non-linear load)
Waveform output	Pure sine
Efficiency	AC mode = 290% when fully loaded Battery mode = 285% when fully loaded ECO mode = 294% when fully loaded
Transfer time	Main - Battery = 0ms Main - Bypass = 24ms
Other features	ECO Mode, LCD information panel, audible warning of possible faults
Battery type	Maintenance-free lead 12V 9.5Ah battery
Recharge time	4 hours to 90% capacity
Dimensions	440 (W) x 86.5 (H) x 430 (D) mm
Weight	14 Kg
Output power point	2 protected backup power points Schuko type
Temp. operation	0°C - 40°C