

SAFIRE LIFEPO LITIUMBATTERI 1280WH RS-485 KOMMUNIKASJON IP67

- Type: Batteri
- Utgangsspenning (volt): 12V
- Utgangsstrøm (ampere): 10A
- Nominell kapasitet (AH/WHA/MAH): 1280wh
- DIN: Nei



Safire - Lithium LiFePo Battery 1280Wh (100Ah) - Integrated MPPT regulator - RS-485 for communication - Can connect to SF-SOLARPANEL-200W

- Safire
- MPPT with integrated battery
- Compatible with Safire solar panel of 200W
- 1280Wh LiFePo battery with 2000 charge and discharge cycles
- Integrated MPPT regulator
- Maximum supported load 20W
- Communication RS485 for third-party integration
- Degree of protection IP67
 Brand
 Material
 Capacity
 Communication

Safire LiFePo 100Ah (1280Wh) RS485 (For integration with third parties). Provides all system information such as load level, system status or power consumption 12.8V Integrated DC Regulator (with standard jack connector compatible with

Nominal voltage

Operating temperature

Cycles Maximum input power Load voltage Maximum current load Maximum load supported Regulator Installation

Installation bracket Degree of protection Battery size CCTV cameras) Charge: 0 °C to 65 °C (32 °F to 140 °F) Discharge: -30 °C to 65 °C (-22 °F to 140 °F) >2000 Up to 450W in total $9\sim12.6V$ 10A 20W Integrated MPPT Can be coupled to the solar panel SF-SOLARPANEL-100W or stand alone In mast between 100-200 mm IP67 205 (W) x 68 (H) x 112 (D) mm