



WWW.SECURITYSYSTEMS.NO

UNI-TREND UT501A



Electrical Insulation Resistance Meter - LCD display up to 2000 accounts - AC voltage measurement up to 750V - Automatic shutdown - Ranges 100V/250V/500V/1000V

- UNI-T
- Electrical Equipment Insulation Resistance Tester
- LCD display up to 2000 accounts
- Insulation resistance measurement (?) of voltages 100V/250V/2500V/1000V
- AC voltage measuring range 30~750V
- Automatic shutdown

Brand

Isolation Resistance

Uni-T

100V: 0M?~100M? ±(3%+5)

250V: 0M?~99.9M? ±(3%+5) / 100M?~5G?
±(5%+5)

500V: 0M?~99.9M? ±(3%+5) / 100M?~5G?
±(5%+5)

1000V: 0M?~99.9M? ±(3%+5) /
100M?~5G? ±(5%+5)

Charging current

50V (R=50k?) 1mA; 0%~10%

100V (R=100k?) 1mA; 0%~10%

250V (R=250k?) 1mA; 0%~10%

500V (R=500k?) 1mA; 0%~10%

Short circuit current	1000V (R=1M?) 1mA; 0%~10% <2mA
Rango de medida de voltaje AC	30V~750V $\pm(2\%+3)$
Dimensiones display	70.6mm x 34mm
Cuentas display	Hasta 2000
Buzzer voltaje alto	Si dispone
Indicador de sobrecarga	Si dispone
Test resistencia interna 10 M?	Si dispone
Dimensiones	100 (Al) x 150 (An) x 71 (Fo) mm
Alimentación	6 x pilas 1.5V (LR6)
Peso	500 g
Seguridad	CAT II 1000V/ CAT III 600V