

ENGENIUS ENS500EXT

EnGenius

Omnidirectional wireless link - Frequency 5.18GHz 5.82GHz - Supports 802.11 b/g/n - IP65, suitable for exterior - Power 400 mW

Outdoor, long range, wireless data link 802.11a/n compliant for data transmission speeds of up to 300 Mbps.

The ENS500EXT is the ideal solution for wirelessly connecting cameras with IP NVR's, working in the 5.4GHz & 5.8GHzGHz frequencies it avoids the usual, saturated, 2.4GHz band. The dual omnidirectional exterior 5dBi antennas, MIMO technology (multiple transmission/reception) and a maximum transmission power of 26dBm (configurable) makes this ideal for wireless bridges of up to several kilometres (exact distance depends on the topology). The 5dBi antenna is omnidirectional (360°).

Con un grado de protección IP65 y rango de temperatura de funcionamiento de -20 a 70°C puede trabajar en exteriores en las condiciones más inhóspitas.

The ENS500EXT can work in several modes, both as an access point and as a wifi client, so with a single device you can implement most wireless network node types with total security: WEP & WAP encryption, WAP2, authentication 802.1x, hidden SSID and MAC address filtering. It supports work mode "point to point" and "point to multi-point".

Web configurable, dual Ethernet ports, PoE injector and the signal level LED's make this an easy to deploy device.